

IMAGETRAC IV SPECIFICATIONS

THROUGHPUT SPEEDS IN LANDSCAPE ORIENTATION

RESOLUTION DPI	8.5X11 IN. PAGES/MINUTE	A4 PAGES/MINUTE	CHECKS PAGES/MINUTE	A6 PAGES/MINUTE
200	366	374	758	587
300	174	178	385	299

MAXIMUM DOCUMENT SIZE	305 mm [12 in.] x 660 mm [26 in.]
MINIMUM DOCUMENT SIZE	64 mm [2.5 in.] x 85 mm [3.25 in.]
PAPER THICKNESS AND WEIGHT	Standard feeder 45 g/m ² to 200 g/m ² ; Asian paper (rice paper) to card stock
FEEDER CAPACITY	1,500 sheets (20# bond paper)

ACCESSORIES	IMAGETRAC IV (FRONT SIDE DOCUMENT)	IMAGETRAC IV (FRONT + BACK SIDE DOCUMENT)
BARCODE READER	Yes	No
PATCH CODE READER	Yes	No
PRE/POST INKJET PRINTER	Pre	Pre and/or Post
MICR - E13B	Yes - front or back	Yes - front or back
MICR - CMC7	Yes - back	Yes - back
DOCNETICS FOR CHARACTER RECOGNITION	Yes	Yes*
DOCNETICS FOR BARCODE RECOGNITION	Yes	Yes*
DOCNETICS FOR DOCTYPE RECOGNITION	Yes	Yes*

MULTI-FEED DETECTION	Single or multiple ultrasonic sensor technology and/or friction multi-feed detection
COLOR TOUCH SCREEN CONTROL	Operator control via 19" color LCD panel touch screen
FILE FORMAT OUTPUT	JPEG (color/grayscale images); JPEG 2000 lossless and lossy; TIFF (black and white images)
OPTICAL RESOLUTION	200/300 dpi
ILLUMINATION	Dual LED illumination patented technology
OUTPUT RESOLUTION	Black and White/Color/Grayscale: 100 to 600 dpi
IMAGE PROCESSING	DynamicTIFF Thresholding; Black and White Speckle Removal; Autocrop; Auto-Deskew; Generous Crop; Image Rotation; Multi-image Output; Color Dropout, etc.
ENVIRONMENTAL FACTORS	RoHS compliant; WEEE
ACOUSTICAL NOISE	Operating mode 77.4db(A)
HEAT DISSIPATION	6,000 to 15,000 BTUs/hour
OPERATING HUMIDITY	20% to 80% non-condensing (percent relative humidity)
OPERATING TEMPERATURE	50 to 90 degrees (F), 10 to 32 degrees (C)
SHIPPING/STORAGE TEMPERATURE	-22 to 140 degrees (F), -30 to 60 degrees (C)
ALTITUDE	Sea level to 15,000 ft (4,500 M)
ELECTRICAL REQUIREMENTS	United States: 208V-, 2 Wire + GND/25A 50/60 Hz; European Union: 230V-, 1 Wire + PE (single phase) 25A 50/60 Hz; Japan: 200V-, 2 Wire + GND/25A 50/60 Hz <i>US Sites - Units shipped with power cord and 208-240V, NEMA #L6-30 connector</i> <i>Non US sites - Power cable supplied by customer to meet local electrical code</i>
APPROVAL AND PRODUCT CERTIFICATIONS	ANSI/UL 60951-1; CSA C22.2#60950-1; CENELEC EN 60950-1; IEC 60950-1; AS/NZS 60950-1
ACCESSORIES	Inkjet printer
DIMENSIONS	Depth: 55 inches; Width: 94 inches; Height: 47.3 inches
WEIGHT	Feeder frame: 232 lbs; Front camera frame: 278 lbs; Rear camera frame: 187 lbs; Pocket frame: 176 lbs
IMAGE OUTPUT	Color: 24 bit JPEG; Grayscale: 8 bit JPEG; Bitonal: 1bit TIFF; Multiple image capture for front and rear camera
POCKETING OPTIONS	Single pocket; Multiple pocket with 2 to 4 pockets per frame
OPTIONAL FEATURES ON SINGLE POCKET UNIT	In-line ICR (Intelligent Character Recognition) for E13B/CMC7: Front camera; barcode reader; Patch code reader; MICR; Pre-inkjet printer
OPTIONAL FEATURES ON MULTIPLE POCKET UNIT	In-line ICR for E13B/CMC7: Front and rear camera; In-line ICR for documents: Front and rear camera; In-line barcode recognition; In-line DocTyping; Barcode reader; Patch code reader; MICR; Pre/post inkjet printer

* Supports advanced printing and sorting capabilities

Specifications are subject to change without notice.

Throughput speeds may vary depending on your choice of driver, application software, operating system and PC.

SoftTrac, ImageTrac and DocNetics are registered trademarks.
DynamicTIFF is a trademark of Imaging Business Machines, LLC.
©2008 Imaging Business Machines, LLC. All rights reserved.